

**Control 400 Standard Coverage Series
Recommended DSP Tunings**



Model	Connection	Protective High-Pass Filter Frequency (Slope 24dB/Oct)	Limiter Voltage	
			RMS (2hrs)	Thermal (100hrs)
Control 412C/T Control 412C/T-VA	Low-Z (8Ω)	65Hz	14 Vrms	12 Vrms
	15W tap	80Hz	Amp's 70V or 100V clipping limiter	
	7.5W tap	65Hz		
	Lower taps	50Hz		
Control 414C/T Control 414C/T-VA	Low-Z (8Ω)	60Hz	17.7 Vrms	14.5 Vrms
	25W tap	70Hz	Amp's 70V or 100V clipping limiter	
	12.5W tap	55Hz		
	Lower taps	45Hz		
Control 416C/T Control 416C/T-VA	Low-Z (8Ω)	55Hz	22.2 Vrms	18.2 Vrms
	30W tap	60Hz	Amp's 70V or 100V clipping limiter	
	15W tap	50Hz		
	Lower taps	40Hz		
Control 418C/T	Low-Z (8Ω)	50Hz	30 Vrms	25 Vrms
	60W tap	60Hz	Amp's 70V or 100V clipping limiter	
	30W tap	45Hz		
	Lower taps	45Hz		
Control 414C/T Micro	Low-Z (8Ω)	65Hz	12.1 Vrms	9.9 Vrms
	10W tap	70Hz	Amp's 70V or 100V clipping limiter	
	5W tap	60Hz		
	Lower taps	60Hz		
Control 414CT MicroPlus	25W tap	70Hz	Amp's 70V or 100V clipping limiter	
	12W tap	60Hz		
	Lower taps	55Hz		

NOTES:

High-Pass Frequencies apply to stated tap setting figure, regardless whether driven by 70V or 100V distributed line.