

# VDO SCEPTRON™ XB

## HIGH-OUTPUT PIXEL-BATTEN

SPEC SHEET



## OVERVIEW

The VDO Sceptron XB is a compact, high-output LED pixel-batten, designed for both lighting and creative video applications. Building on the legacy of the Martin VDO Sceptron family, it inherits all of its benefits such as user-friendly mapping through Martin's P3 System Controller, the ability to exchange diffusers and lenses, and a wide range of available rigging accessories. The VDO Sceptron XB raises the bar with significantly boosted lumen output, enhanced cabling freedom, and the ability to be controlled as a lighting fixture via Art-Net and sACN, and as a creative video element via P3, or both simultaneously. With best-in-class performance, unmatched versatility, and a future-proof design, VDO Sceptron XB is ideal for lighting designers, rental houses, and installation professionals while setting a new standard for powerful, flexible lighting and creative video applications.

## KEY MESSAGES

### FAMILIAR USABILITY, SIMPLIFIED INTEGRATION

VDO Sceptron XB features the same form factor as its predecessor model and generates the same type of effect so it can be easily integrated into designs with the same confidence for successful outcomes as previous applications. It is also completely compatible with all its predecessor diffuser and rigging accessories.

### PRECISION LIGHT QUALITY AND COLOR BOOST TECHNOLOGY

VDO Sceptron XB's enhanced light quality (CRI / TM-30 / TLCI) makes it ideal for illuminating people and spaces with precision. Martin's integrated Color Boost Technology ensures 2.5 to 5 times more brightness in colors. The series also renders much richer and deeper saturated colors by utilizing Extended Gamut Color Calibration.

### SIGNIFICANTLY ENHANCED LUMEN OUTPUT

VDO Sceptron XB more than doubles white lumen output of its predecessor model, allowing it to work as a "lighting fixture" and not just a "decorative LED strip", while output on colors has increased even more.

### EASIER TO DEPLOY AND CONTROL

For the ultimate in flexibility, VDO Sceptron XB can be used as a lighting fixture using Art-Net and sACN, as a creative video element using Martin P3 control, or both at the same time using P3 Mix. It features the latest generation of control options, including FX Macros, color temperature control and tint control. It is also supported by both indoor (P3 PowerPort 2000) and outdoor (P3 PowerPort 500 IP Rental) power supply accessories, while offering more cabling freedom, featuring longer and split cable runs.

# VDO SCEPTRON™ XB

## HIGH-OUTPUT PIXEL-BATTEN

SPEC SHEET

### FEATURES

- Extremely compact and lightweight
- More than double the output of VDO Sceptron 10
- RGBW LEDs (higher output and higher light quality [CRI / TM-30 / TLCI])
- Full Gamut Pixel Calibration (pixel-to-pixel and fixture-to-fixture consistency, even when products from different manufacturing batches are being used together)
- Art-Net, sACN & Martin P3 control (usable as a lighting fixture and as a creative video element)
- Easy mapping and addressing through P3 System Controller or Companion Desktop
- P3 Mix channel enabling switching and fading between "lighting mode" and "video mode"
- IP65-rated for temporary outdoor use
- Stand-alone mode for applications without a Controller
- Wide range of optical accessories, including diffusers and lenses offering many different uses and looks
- Versatile rigging accessories, allowing easy mounting of fixtures in many different configurations
- Indoor and outdoor power+data solutions available (P3 PowerPort family)

### ORDERING INFORMATION

- VDO Sceptron XB 1000 mm, in cardboard box....P/N MAR-90357902
- VDO Sceptron XB 320 mm, in cardboard box.....P/N MAR-90357901
- Flightcase for 10 x VDO Sceptron XB 1000 mm / 30 x VDO Sceptron XB 320 mm .....P/N MAR-91515066
- Flightcase Extender for 10 x VDO Sceptron XB 1000 mm / 30 x VDO Sceptron XB 320 mm .....P/N MAR-91515067
- VDO Sceptron Flightcase to XB Foam Upgrade Kit .....P/N MAR-91515068

#### INCLUDED ITEMS

- Square Diffuser
- Square Smoked Diffuser
- 2x Cable Clip
- Safety Cable Attachment Eyelet
- Multi-Language Safety and Installation Manual

#### RELATED ITEMS

- P3-175 System Controller .....P/N MAR-90721100
- P3-275 System Controller .....P/N MAR-90721101
- P3-PC System Controller .....Free download from [www.martin.com](http://www.martin.com)
- Martin Companion Firmware Upload, Addressing and Stand-Alone Programming Software .....Free download from [www.martin.com](http://www.martin.com)



# VDO SCEPTRON™ XB

## HIGH-OUTPUT PIXEL-BATTEN

SPEC SHEET

### ACCESSORIES

- Magnetic Test Tool, set of 10 ..... P/N 91610139
- VDO Sceptron Diffuser Lens Removal Jaws ..... P/N 91611836

#### RIGGING ACCESSORIES

- VDO Sceptron Sliding Brackets, set of 10 ..... P/N 91610123
- Super Lightweight Half Coupler Rigging Clamp, black ..... P/N 91602018
- Low Profile VDO Sceptron Half Coupler ..... P/N 91611790
- VDO Sceptron Linear Aligners, set of 10 ..... P/N 91610124
- VDO Sceptron Linear Coupler ..... P/N 91611843
- VDO Sceptron Parallel Couplers, 30/40/50 mm, set of 10 ..... P/N 91610125
- VDO Sceptron Parallel Couplers, 60/70/80 mm, set of 10 ..... P/N 91610138
- VDO Sceptron Spigot Adapter, 28 mm ..... P/N 91611791
- VDO Sceptron Floorstands, set of 2 ..... P/N 91611792
- VDO Sceptron Pivot Coupler ..... P/N 91611793
- Safety Cable, SWL 60 kg, BGV C1 / DGUV 17, black ..... P/N 91604006
- Safety Cable, SWL 60 kg, BGV C1 / DGUV 17, silver ..... P/N 91604007
- Set of 10 VDO Sceptron XB Cable Clips ..... P/N MAR-91616139

#### DIFFUSERS AND LENSES 320MM

- VDO Sceptron Flat Diffuser 320 mm ..... P/N 91610111
- VDO Sceptron Flat Smoked Diffuser 320 mm ..... P/N 91610113
- VDO Sceptron Round Diffuser 320 mm ..... P/N 91610115
- VDO Sceptron Round Smoked Diffuser 320 mm ..... P/N 91610117
- VDO Sceptron Square Diffuser 320 mm ..... P/N 91610119
- VDO Sceptron Square Smoked Diffuser 320 mm ..... P/N 91610121
- VDO Sceptron Tube Diffuser 320 mm ..... P/N 91611630
- VDO Sceptron Tube Smoked Diffuser 320 mm ..... P/N 91611650
- VDO Sceptron XB Lens 10 degrees 320 mm ..... P/N TBC
- VDO Sceptron XB Lens 20 degrees 320 mm ..... P/N TBC
- VDO Sceptron Glare Shield 320 mm ..... P/N MAR-91616137

#### DIFFUSERS AND LENSES 1000MM

- VDO Sceptron Flat Diffuser 1000 mm ..... P/N 91610112
- VDO Sceptron Flat Smoked Diffuser 1000 mm ..... P/N 91610114
- VDO Sceptron Round Diffuser 1000 mm ..... P/N 91610116
- VDO Sceptron Round Smoked Diffuser 1000 mm ..... P/N 91610118
- VDO Sceptron Square Diffuser 1000 mm ..... P/N 91610120
- VDO Sceptron Square Smoked Diffuser 1000 mm ..... P/N 91610122
- VDO Sceptron Tube Diffuser 1000 mm ..... P/N 91611640
- VDO Sceptron Tube Smoked Diffuser 1000 mm ..... P/N 91611660
- VDO Sceptron XB Lens 10 degrees 1000 mm ..... P/N TBC
- VDO Sceptron XB Lens 20 degrees 1000 mm ..... P/N TBC
- VDO Sceptron Glare Shield 1000 mm ..... P/N MAR-91616138

#### POWER AND DATA SUPPLY UNITS

- P3 PowerPort 2000 ..... P/N MAR-90721200
- P3 PowerPort 500 IP Rental ..... P/N MAR-90721201
- P3 PowerPort 500 IP Install ..... P/N MAR-90721202
- DCE PSU 240 IP ..... P/N MAR-90721203

#### DATA SPLITTER & BOOSTER FOR SPLIT OR EXTENDED CABLE RUNS

- DCE DataSplitterBooster IP ..... P/N MAR-90721204

#### PRE-ASSEMBLED HYBRID DCE CABLES

- DC + Ethernet Cable DCE-DCE 1m ..... P/N MAR-91700100
- DC + Ethernet Cable DCE-DCE 2.5m ..... P/N MAR-91700101
- DC + Ethernet Cable DCE-DCE 5m ..... P/N MAR-91700102
- DC + Ethernet Cable DCE-DCE 10m ..... P/N MAR-91700103
- DC + Ethernet Cable DCE-DCE 25m ..... P/N MAR-91700104

#### BULK HYBRID DCE CABLES

- DC + Ethernet Cable 100m ..... P/N MAR-91700105
- DC + Ethernet Cable LSZH 100m ..... P/N MAR-91700106

# VDO SCEPTRON™ XB

## HIGH-OUTPUT PIXEL-BATTEN

SPEC SHEET

### ACCESSORIES (CONTINUED)

#### FIELD-INSTALLABLE DCE CONNECTORS

- Field-installable Connector DCE Male ..... P/N MAR-91700107
- Field-installable Connector DCE Female ..... P/N MAR-91700108




#### CLOSING CAPS FOR DCE CONNECTORS

- Closing Cap Male DCE Connector ..... P/N MAR-91700109
- Closing Cap Female DCE Connector ..... P/N MAR-91700110



#### HYBRID DCE ADAPTERS

- DC + Ethernet Adapter DCE Male-Male ..... P/N MAR-91700111
- DC + Ethernet Adapter DCE Female-Female ..... P/N MAR-91700112
- DC + Ethernet Adapter EtherCON+Wires to DCE ..... P/N MAR-91700113
- DC + Ethernet Adapter DCE to EtherCON ..... P/N MAR-91700114



# VDO SCEPTRON™ XB

## HIGH-OUTPUT PIXEL-BATTEN

SPEC SHEET

### TECHNICAL SPECIFICATIONS

#### CONTROL AND PROGRAMMING

Control Protocols.....Art-Net, RDM over Art-Net, sACN and Martin P3

Protocol Detection.....Automatic

##### DMX Modes 1000mm Variant:

Compact, Basic, Extended 5 Segments, Extended 10 Segments, Extended 25 Segments, Extended 100 Pixels, Compact Direct, RGB, PixelMap 5 Segments, PixelMap 10 Segments, PixelMap 25 Segments and PixelMap 100 Pixels

##### DMX Modes 320mm Variant:

Compact, Basic, Extended 2 Segments, Extended 4 Segments, Extended 8 Segments, Extended 32 Pixels, Compact Direct, RGB, PixelMap 2 Segments, PixelMap 4 Segments, PixelMap 8 Segments and PixelMap 32 Pixels

##### DMX Channels 1000mm Variant:

8, 14, 29, 44, 89, 314, 8, 3, 15, 30, 75, 300

##### DMX Channels 320mm Variant:

8, 14, 20, 26, 38, 110, 8, 3, 6, 12, 24, 96

##### 16-bit Controllable Parameters.....

Dimming

Setting and Addressing.....Martin P3 or RDM over Art-Net

Fixture identification.....User-settable ID number

Art-Net Compliance.....Art-Net 1, 2, 3 and 4; including RDM over Art-Net

sACN Compliance.....ANSI E1.31 - 2018

Martin P3 Compliance:.....P3 System Controller Software 6.1.0 or newer

Ethernet Transceiver.....10/100Mbit

Firmware Update.....via Ethernet using Martin Companion or P3 System Controller

#### CONTROL/USER INTERFACE

Device status .....Multi-color visual indication

Device test and reset .....Magnetic pushbutton to call up local test patterns and reset device

#### OPTICS

Pixel Pitch.....10.00 mm

Pixel Quantity 1000mm Variant.....100 RGBW pixels

Pixel Quantity 320mm Variant.....32 RGBW pixels

LED Type.....Single RGBW LED per pixel

Beam Angle .....125 Degrees (half peak)

Field Angle.....160 Degrees (one-tenth peak)

Minimum LED lifetime: >50,000 hours (to >70% luminous output)\*

\*Figure obtained under manufacturer's test conditions

#### PHOTOMETRIC DATA

Luminous Output Mixed White .....2300 lumen / m

Luminous Output Red .....640 lumen / m

Luminous Output Green .....1940 lumen / m

Luminous Output Blue .....350 lumen / m

Luminous Output Mixed White half power mode .....1250 lumen / m

Luminous Output Red half power mode .....320 lumen / m

Luminous Output Green half power mode .....970 lumen / m

Luminous Output Blue half power mode .....175 lumen / m

Luminous Intensity Mixed White .....880 cd/m

CCT .....Variable 1,800 K - 12,850 K (+/- 200 K)

CRI (Color Rendering Index).....≥ 75

CQS (Color Quality Scale) .....≥ 86

TM-30 Rf

(IES TM-30-15 Fidelity Index).....≥ 80

TM-30 Rg

(IES TM-30-15 Gamut Index) .....≥ 114

TLCI (Television Lighting

Consistency Index) .....≥ 68

LED Refresh Rate .....1,001 Hz or 4,004 Hz (selectable)

Binning .....Tight color and flux binning

Calibration .....Full Gamut Pixel Calibration

Color Modes .....Direct Color Mode, Extended Gamut Mode, Calibrated Color Mode & Linear Video Mode

\* All Photometric Data measured in steady state (30 minutes warm-up time) at 25°C ambient

\* All Photometric Data measured at 6500 K white

\* All Photometric Data without diffuser/lens installed

#### OPTICAL ACCESSORIES

- Flat Diffuser
- Flat Smoked Diffuser
- Round Diffuser
- Round Smoked Diffuser
- Square Diffuser
- Square Smoked Diffuser
- Tube Diffuser
- Tube Smoked Diffuser
- 10 Degree Lens
- 20 Degree Lens
- Glare Shield

All optical accessories are interchangeable and clip onto fixtures

# VDO SCEPTRON™ XB

## HIGH-OUTPUT PIXEL-BATTEN

SPEC SHEET

### TECHNICAL SPECIFICATIONS

#### DYNAMIC EFFECTS

Dimmer/Shutter	0 — 100% continuous dimming, regular and random strobe, instant open and blackout
Dimming options	Choice of four dimming curves
Color mixing	RGBW, independently variable 0 - 100%
Color temperature control	Variable 1,800 — 12,850 K
Tint control	Variable green-magenta shift $\Delta$ uv -0.05 — +0.05
Virtual Color wheel	48 color presets, continuous rotation & random color
PixelMapping	Individual RGB control of each pixel
P3 Mix	Videomapping of fixture with variable crossfade between DMX control and video control
Pre-programmed effects	Various pre-programmed FX; featuring foreground color, background color, speed and direction control
LED Frequency control	Two LED PWM control modes

#### P3 VIDEO PROCESSING

System processing depth	16 bits per color (64 bits per pixel)
Frame rate	up to 60 frames/sec
Brightness control	0-100% (maintaining full color depth)
Latency between first and last fixture	None
Gamma Curve Control	Yes, adjustable
Image Control Parameters	Hue, Saturation, Brightness, Contrast, Lowlight & Gain
Color temperature control	Variable 1,800 — 12,850 K
Tint control	Variable green-magenta shift $\Delta$ uv -0.05 — +0.05
Color Gamut Control	Real-time

#### STAND ALONE PROGRAMMING

Programming Interface	Martin Companion Application via RDM over Art-Net
Controllable Parameters	All, including internal FX
Maximum Number of Scenes	20
Hold Time	Global or per scene
Fade Time	Global or per scene
Synchronization	Yes, including synchronization across different fixture types

#### CONSTRUCTION

Color	Matte black
Base	Aluminum
Protection rating	IP65
Corrosion Resistance	ISO 12944-6: 2018; C3 High, Test regime ISO 9227, 240h

#### INSTALLATION

Mounting	Channel for M6 captive nuts on back of profile
Mounting options	M6 bolts, sliding bracket, half coupler, spigot adapter, linear coupler, pivot coupler, parallel coupler or floorstand
Orientation	Any
Maximum vertical column height	8 fixtures
Location	indoor or temporary outdoor use

#### CONNECTIONS

DC Power and Network input	cable tail with DCE hybrid connector (7pin)
DC Power and Network thru	cable tail with DCE hybrid connector (7pin)
All Connections Hot plugging compatible	

#### ELECTRICAL

Nominal input voltage	48 VDC +/- 4%
Power supply options	P3 PowerPort 2000, P3 PowerPort 500 IP Rental, P3 PowerPort 500 IP Install, DCE PSU 240 IP or generic 48 VDC PSU
Power Consumption 1000 mm Variant:	
Typical Full Power Mode	30.0 W *
Typical Half Power Mode	16.8 W *
Idle	3.2 W *
Hibernation	1.6 W *

#### Power Consumption 320 mm Variant:

Typical Full Power Mode	10.4 W *
Typical Half Power Mode	6.4 W *
Idle	2.1 W *
Hibernation	1.6 W *

\* Measurements made at nominal voltage. Allow for a deviation of +/- 10%.  
Typical: fixture at full output white.  
Idle: fixture at zero output.  
Hibernation: no output, wake-up procedure required to re-use fixture.

#### THERMAL

Cooling	Convection
Maximum ambient temp. (Ta max.)	55° C (131° F)
Minimum ambient temp. (Ta min.)	-30° C (-22° F)
Typical Heat Dissipation 1000 mm variant (calculated, +/- 10%)	102 BTU/hr.
Typical Heat Dissipation 320 mm variant (calculated, +/- 10%)	35 BTU/hr.

# VDO SCEPTRON™ XB

## HIGH-OUTPUT PIXEL-BATTEN

SPEC SHEET

### TECHNICAL SPECIFICATIONS

#### ENVIRONMENTAL

RoHS .....	Compliant
REACH .....	Compliant
WEEE .....	Compliant
Proposition 65 .....	Compliant
FSC .....	Certified cardboard inlay and outer packaging
Efficacy (max output) .....	76.7 lm/W
LWR* .....	1438 lm/kg (657 lm/lbs.)

\* LWR = Lumen-to-Weight Ratio

#### APPROVALS

- Global CB Certification/IECEE: IEC 62368-1
- EU Safety: IEC 62368-1
- EU EMC: EN 55032; EN 55035; EN 61000-3-2, EN 61000-3-3
- US Safety: UL 62368-1
- US EMC: FCC Part 15 Class B
- Canadian safety: CSA C22.2 No.62368-1
- Canadian EMC: ICES-003 Class B
- Australia/NZ: RCM
- United Kingdom: UKCA
- India: BIS IS 10322(Part5/section7) - Pending



### Fixture / Optical Accessories

All dimensions are in mm

